## WHEEL-BALANCERS - PASSENGERS' CARS

#### Eye-catching graphics, updated software for a great user experience.















www.giuliano-automotive.com

#### DIGITAL ELECTRONIC 3-D WHEEL-BALANCER WITH VIDEO DISPLAY, LASER LINE AND LED LIGHT

Advanced software

for further upgrades.\*

USB port for firmware updating via pen-drive.

Flat screen HD color video monitor 19" TFT. Precise, reliable and easy to use software.

#### **FUNCTIONS** -

- Automatic measuring of wheel diameter and distance
- Automatic START and STOP
- Static and dynamic balancing
- OPTIMATCH function
- Self-diagnosis and selfcalibration
- Optimization of static unbalance
- CLIP system for application of stick-on weight



#### **LED LIGHT** to illuminate working area.



#### LASER LINE for exact positioning of adhesive weights.

A very practical Wheel Lifter reduces effort and increases productivity (optional).

Pedal brake

Complete with Wheel guard, cones and quick clamping ring nut

Automatic measuring of wheel width by **SONAR** (LA), standard.

#### SPECIAL ALU-S PROGRAMS



Programs for selecting the best correction planes for any kind and shape of alloy rim.

#### **SELF SELECTION MODE**



Self-recognition of the Working program.

#### HIDDEN WEIGHT





 Fast & Easy Split (FES) function, is really the fastest method on the market to split balancing weights behind the spokes of your aluminum wheel.

#### **OPPOSITE WEIGHT FUNCTION (OPF)**





 Opposite Weight function (OPF), enables to place the balancing stick-on weight on the lower inside part of the

**EXTENSIVE SELECTION OF** 

aluminum wheel (at 6:00).

\*The performance of the machine over time can improve, thanks to targeted updates.

### STANDARD ACCESSORIES

#### **OPTIONAL ACCESSORIES**



- Wheel clamping adaptors
- Clamping cones with spacers
- Wheel lifter

Find out more on our website!

#### STANDARD FEATURES -

Max. wheel weight	75 kg
Max. wheel diameter	1100 mm
Rim diameter	10"-30" / 255-765 mm
Rim width	1,5"-20" / 40-510 mm
Power supply	230V 1ph (50/60) Hz
Unbalance detection time	4,7 s (5 3/4"x14") 15 kg
Balancing speed	< 150 rpm
Balancing precision	÷ 1 g
Net weight with guard	102 Kg
Max. overall dimensions	1350x1150x1440÷1540 mm

# Available in: ● Blue Trim ● BlackTrim ● Red Trim

#### STANDARD ACCESSORIES









Wheel guard Manual gauge for measuring wheel rim width . Cones and quick clamping ring nut • Counterweight pliers