

The best choice for the average tyre shop with budget goal.

NEW

SL22 PRO LL



Discover on our website!

AUTOMATIC LEVER - NO LEVER TILT BACK TYRE CHANGER WITH DUAL ASSIST ARM FOR CAR WHEELS 10" – 24"



Suitable for Tubeless tyre bead seating system (optional)

✓ Tyre inflation by pedal (standard)

✓ Equipped with **LL LEVERLESS** tyre mounting/demounting system



"LEVERLESS" MODE



Control lever to manage movements of the tool.

✓ Tabletop thickness 12 mm



1010 mm 390 mm 10" - 22" 12" - 24"

✓ Tilting tower, sliding horizontal arm with \varnothing 41 mm operating arm

NEW

HP4 Additional auxiliary helper system provides a valuable support in mounting/demounting Run Flat, UHP and low profiled tyres.



HP4 Dual Assist Arm with 3 tools (standard):

- Bead Pressing Roller
- Bead Lifting Roller
- Bead Pressing Pad

Additional tilting roller tool for lower bead with an anti-collision joint.

✓ Bead breaker **double effect** Cylinder \varnothing 200 mm., made in aluminum

✓ Reinforced Chassis



Efficiency and Speed with double rotation speed (3ph Version)

STANDARD FEATURES

Rim clamping from outside	10" - 22" *
Rim clamping from inside	12" - 24" *
Max. tyre diameter	1010 mm (39")
Max. tyre width	390 mm (15")
Bead breaker cylinder force at 10 Bar	30800 N
Operating pressure	10 bar (145 Psi)
Power supply	400V-3ph-2 speed
	220V-1ph
Motor power	0,75/1,125 KW (400V-3Ph-2V)
	0,90 KW (230V-1Ph)
Rotation speed	7 - 14 rpm
Pre-set tyre inflating pressure	3,5 bar (50 Psi)
Net weight	318 kg
Max. overall dimensions	1420x1740x2230 mm

* By adjustable jaws

STANDARD ACCESSORIES

- Lubricator + pressure regulator
- Bead lifting lever
- Plastic protectors for LL mounting/demounting tool
- Pedal operated inflating device